



4Mpx IR Camera

Latest generation CCTV camera that will ensure the highest security at entry/exit points as well as in any part of the car park.

Main features:



- 2688×1520 High resolution
- IP67
- Real-time HD video
- IR range of up to 30 metres
- Vari-focal lens
- DWDR & 3D DNR & BLC

Technical specifications:

REFERENCE	
07000810	
CAMERA	
Image sensor	CMOS 1/3" Progressive Scan
Min. lighting	0.01Lux @(F1.2,AGC ON), 0.014 Lux @(F1.4,AGC ON), 0 Lux with IR
Shutter time	1/3s ~ 1/10,000s
Lens	2.8 - 12 mm @ F1.4, angle of view: 112°~33.8°
Day & night	IR cut filter with auto switch
Wide dynamic range	Digital WDR
Digital noise reduction	3D DNR
Background light compensation	Yes
COMPRESSION STANDARD	
Video compression	H.264/MJPEG/H.264+
Bit rate	32 Kbps – 16 Mbps
IMAGE	
Maximum image resolution	2688 × 1520
Frame rate	50Hz:Main stream:20fps(2688×1520),25fps(1920×1080), 25fps(1280×720), Sub stream:25fps(352×288),25fps(640×360) 60Hz: Main stream:20fps(2688×1520),30fps(1920×1080),30fps(1280×720),Sub stream: 30fps(352×240),30fps(640×360)
INTERFACE	
Communication interface	Port Ethernet 1 RJ45 10 M / 100 M
GENERAL	
Operating conditions	-30 °C – 60 °C (-22 °F – 140 °F), Humidity 95% or less (non-condensing)
Power supply:	12V DC±25%, PoE (802.3af Class3) , Max. 5.5 W (Max. 7.5 W with IR cut filter on)
Power consumption:	Max. 5,5 W (7.5W with IR cut filter on)
Protection:	IP67
IR Range	Approx 20 to 30 meters(65.6-98.4ft)
Size	95×105×258.6 mm (3.74" × 4.13" × 10.18")
Weight	1200 g